



TECHNICAL INFORMATION



Substrates

Titan

Acrylic

Quickset

Envirotech

Permabind

	Titan	Acrylic	Quickset	Envirotech	Permabind
Bond	E	E	E	E	E
Vellum	E	G, D	E	G, D	E
Index	E	G, D	E	G, D	E
Uncoated Board	E	G, D	E	G, D	E
Enamel	E	G, D	E	G	E
Cast Coated	G	G, D	G	G, D	E
Dull Coated	G, D	G, D	G, D	G, D	E
Acetate	NR	NR	NR	NR	E
Kimdura	NR	NR	NR	NR	G, S
Tyvek	NR	NR	NR	NR	F, S
Vinyl	NR	NR	NR	NR	G, S
Currency Cover	NR	NR	NR	NR	E

Press Type

Titan

Acrylic

Quickset

Envirotech

Permabind

	Titan	Acrylic	Quickset	Envirotech	Permabind
Duplicator Conventional Dampening System	G	E	E	E	E
Duplicator Integrated Dampening System	G	E	G	E	G
22" and Larger	E	F	G	F	E
No Heat Web	NR	G, D	F	G	NR

Plate Type

Titan

Acrylic

Quickset

Envirotech

Permabind

	Titan	Acrylic	Quickset	Envirotech	Permabind
Electrostatic	NR	E	F	E	F, S
Silvermaster	G	E	G	E	E
Onyx	F	E	G	E	G
Megalith	G	E	G	E	E
Metal	E	E	E	E	E

Titan

Acrylic

Quickset

Envirotech

Permabind

	Titan	Acrylic	Quickset	Envirotech	Permabind
Tack @ 800 rpm	11 - 14	15 - 16	10 - 15	15 - 16	15 - 16
Laser Safe	Yes	NR	Yes	NR	Yes
Available Can Size	5 Lb	1 Lb & 5 Lb	1 Lb & 5 Lb	1 Lb & 5 Lb	1 Lb & 5 Lb

E = Excellent G = Good F = Fair NR = Not Recommended

D = Drier may be required (Add 1/2 oz per pound of Spinks D18 Twin Dry)

S = Submit Stock Samples to Laboratory to confirm compatibility

For technical questions call Spinks at 800-327-INKS